

# Domissima

BUILT  
BY  
EXPERTS

# Domoreflex Primer



## Acrylic water-based primer

DOMOREFLECT PRIMER is an eco-friendly, acrylic, water-based primer, for external and internal, horizontal and vertical surfaces, suitable for the DOMOREFLECT products and for the SERITAL PT and SERITAL PT W varnishes. It waterproofs and stabilizes the substrate, thus improving the adhesion of coatings, paints and varnishes and maximizing their performance.

### Field of application

DOMOREFLECT PRIMER is suitable for priming on:

- Any surfaces, external and internal, which stabilization of the substrate and adhesion improvement is required.
- Surfaces which DOMOREFLECT products are to be applied.
- Microcement coatings which SERITAL PT or SERITAL PT W products are to be applied.

### Advantages

- Waterproofs the substrate's surface.
- Dries quickly.
- Improves the adhesion of the paint.
- Eco-friendly, solvent-free.
- Stabilizes the substrate.
- Easy to use.
- Water vapor permeable but not water permeable.

### Method of use

#### Substrate condition

Must prepare the substrate in order to be clean of loose pieces, as well as peeled off paints and oils.

#### Application

On porous surfaces apply the DOMOREFLECT PRIMER in proportion to water 1:2, and to non-porous surfaces in a ratio of 1:3 to prevent film formation.

After dilution, apply with roller, brush or spray.

### Yield

10-14 m<sup>2</sup>/L depending on the nature of the substrate.

### Storage

It can be retained at least 12 months from its production day, in its package, in cool environment and protected from frost and direct sunlight.

### Packaging

Pails of 1 L, 3 L & 10 L.

### Volatile Organic Compounds

EU REGULATION 2004/42: According to Directive 2004/42/EU (Annex II, Table A), the maximum allowed content of VOC (Product Category h / Type WB) is 30 g/L (limits of 2010) for the final product. The final DOMOREFLECT PRIMER contains max <30 g/L.

### Specifications

Form	Liquid
Shading/Colors	Clear
Specific weight	1.02 ± 0.03 kg/L (23°C)
Application Temperature	+5°C to +35°C

All the technical data stated in the present Technical Data Sheet are based on laboratory tests and the knowledge and experience of the company. Different conditions may apply at field applications that are beyond the control of the company. Therefore, the end user is ultimately responsible to make sure that the product is suitable for the application in question and to know the real conditions of the project.