

SOPRADERE

Description

SOPRADERE is a ready-to-use cold-applied bitumen primer composed of bitumen, volatile solvents and adhesive additives. In accordance with DTU 43 (NF P 84-204).

Characteristics

	SOPRADERE
Aspect	Black homogenous liquid, leaving a slightly sticky black film once dry
Dry content	> 40 % of weight
Density at 20 °C	940 kg/m ³
Viscosity cup n° 6 at 20°C	20 to 25 sec
Flash point (ASTM D 56)	+ 30°C
Drying time on concrete	Less than 1 hour

Packaging & consumption

Cans: 5 kg or 30 kg.

Approximate consumption: 250 g/m²

Depends on nature of use and the nature of the substrate.

On rough and absorbent substrate (i.e. concrete, wood):

- 30 liters can covers about 120 m²
- 5 liters can covers about 20 m²

On smooth, non-absorbent substrate (i.e. metal), the average consumption may be lower.

Storage:

The product can be store until 12 months, ensure that it is kept above 0°C and away from sun rays.

User application

SOPRADERE is used as a cold-applied primer, to increase adherence for bitumen-based waterproofing membranes in compliance with **DTU 43**. It is also used as a bituminous coating for buried walls and foundations.

All the applications are described in the French Standards DTU, Technical Guidelines or Technical Approvals. For further details refer to specific technical information.

Installation

Product must be well mixed in order to obtain a proper homogenization of components. Ensure that the tools are clean.

It will be applied with a brush or roller onto dry, clean surfaces, free of non-adhesive materials.

Metal surfaces must be degreased beforehand.

Let the product dry completely before applying waterproofing membranes.

Tool cleaning : Cleaning solvents (i.e. White Spirit, Xylene).

Special indications

Hygiene, health and environment:

- Flammable: keep away from flames and sparks during use.
- Ensure that all cans, empty or full, containing flammable substances are kept at least 10 m away. Do not pierce the lid under any circumstances.
- If spray gun is used, ensure that no incompatible material is used that may create sparks.
- Do not breathe in fumes.
- Avoid the product coming in contact with eyes.
- Do not smoke while product is being used.
- Do not throw waste into drains

For more information, please refer to the relevant Safety Data Sheet.

Quality control:

SOPREMA has always attached the highest importance to Quality Control.

For this reason, we operate an independently monitored Quality Assurance System in compliance with **BS EN ISO 9001**, certified by **BSI Management System**.

